

Sl. No.	Tests	Minimum Quantity Required	Test Charges (Rs.) per Sample
*	FLAMMABILITY TESTING		
	General Apparel		
81)	Ease of ignition of vertically oriented specimen [BS EN ISO 6940]	0.50 m	1800
82)	Flame spread properties of vertically oriented specimen	0.50 m	1800
	➤ BS EN ISO 6941	0.50 m	1800
	➤ DIN EN ISO 6941	0.50 m	1800
	➤ BS EN 1103	0.50 m	2000
83)	UK night wear safety regulation		
	➤ BS 5438 / BS 5722 Test 1	0.50 m	1800
	➤ BS 5438 / BS 5722 Test 2	0.50 m	1800
	➤ BS 5438 / BS 5722 Test 3	0.50 m	1800
	Curtain, Drapes and Blinds		
84)	Ignitability of vertically oriented specimen [BS EN 1101]	0.50 m	1800
85)	Flame spread properties of vertically oriented specimen [BS EN 1102]	0.50 m	1800
	Personal Protective Clothing		
86)	Limited flame spread [EN 532 / ISO 15025]	0.50 m	1800
87)	For limited flame spread		
	➤ BS 5438: 1976 Test 1	0.50 m	1800
	➤ BS 5438: 1976 Test 2	0.50 m	1800
	➤ BS 5438: 1976 Test 3	0.50 m	1800

Non-members

Sl. No.	Tests	Minimum Quantity Required	Test Charges (Rs.) per Sample
	➤ BS 5438: 1976 Test 3	0.50 m	1800
88)	Limiting Oxygen Index - IS:13501/ASTM D 2863	0.50 m	1800
89)	Vertical Flammability - IS:11871 / BS:3119 / NFPA 1975 / NFPA 2112	0.50 m	1400
90)	Horizontal Flammability - IS:15061 / ASTM D:5132 / FMVSS / SUZUKI	0.50 m	1400
91)	45°C Inclined Flammability - 16 CFR 1610 / ASTM D:1230 / IS:11871(B)	0.50 m	1400
92)	Carpet Flammability - ASTM D:2859 / 16 CFR 1630 / ISO:6925 / BS : 6307	0.50 m	1000
93)	Vinyl Coated Fabric Flammability - IS:1259	0.50 m	1000
	Flammability of plastics		
94)	Vertical Burning Test [Charges Inclusive of Oven Conditioning]		
	➤ UL 94 (VO.V1.V2)/ ASTM D:3801/ IEC 60695-11-10(B)/ ISO:1210(A)	0.50 m	3000
	➤ UL 94 (VTM)/ ASTM D: 4804 / ISO:9773 (Non Rigid Sample)	0.50 m	3000
	➤ UL 94 (5V)/ASTM 5048 / IEC 60695-11-20	0.50 m	3000
	➤ UL 94 HB		2000
	➤ UL VI		3000
95)	Horizontal Burning Test (Wing Top Method) - ASTM D:4986 / ISO:3582 / ISO:9772	0.50 m	3000
96)	Horizontal Burning Test - UL94HB / ISO:1210(A) / ASTM D:635 / IEC:60695-11-10(A)	0.50 m	1500
97)	Toxicity Index Test as per NCD 1409		36000
98)	Smoke Visibility Test as per UIC 564.2 - Appendix-15		8000