

Sl. No.	Tests	Minimum Quantity Required	Test Charges (Rs.) per Sample
✓	<b>AUTOMOTIVE TEXTILES</b>		
192)	Mass per square metre [ASTM D: 5261]	1 m <sup>2</sup>	500
193)	Thickness [ASTM D: 5199]	0.5 m <sup>2</sup>	500
194)	Abrasion Resistance: Taber [Automotive Std.] up to 300 cycles		
	➤ CS10 Wheel		3500
	➤ Other Wheels		2000
195)	Flammability at 45 <sup>o</sup> [IS: 11871 B / 16 CFR1610 / ASTM D: 1230]	1 m <sup>2</sup>	1400
196)	Horizontal Burning Rate [FMVSS: 302 / IS: 15061]	1 m <sup>2</sup>	1400
197)	Pill (Methanamine) Test [IS: 5641 / ASTM D: 2859]	1 m <sup>2</sup>	1000
198)	Relaxation Shrinkage	1 m <sup>2</sup>	250
199)	Thermal Shrinkage	1 m <sup>2</sup>	750
200)	Odour Test [SNV: 195651]	1 m <sup>2</sup>	1000
201)	Tensile Strength [Automotive Std.]	1 m <sup>2</sup>	1000
202)	Tear Strength [Automotive Std.]	1 m <sup>2</sup>	1000
203)	Stretch and set		1200
204)	Colour Fastness to Light (up to 6) [IS: 2454]	0.25 m <sup>2</sup>	2500
205)	Colour Fastness to Crocking	0.5 m <sup>2</sup>	250
206)	Colour Fastness to Shampooing	0.25 m <sup>2</sup>	600

<b>Sl. No.</b>	<b>Tests</b>	<b>Minimum Quantity Required</b>	<b>Test Charges (Rs.) per Sample</b>
<b>207)</b>	Colour Fastness to Resistance to Cold	0.5 m <sup>2</sup>	
	➤ 20°C for 2 hours		<b>1000</b>
	➤ 30°C for 6 hours		<b>2000</b>
<b>208)</b>	Pliability	0.5 m <sup>2</sup>	<b>500</b>
<b>209)</b>	Blocking Test	0.5 m <sup>2</sup>	<b>750</b>
<b>210)</b>	Gelling Test	0.5 m <sup>2</sup>	<b>500</b>
<b>211)</b>	Flexing Test [Dematia Method]	1 m <sup>2</sup>	
	➤ Up to 50,000 Cycles [IS: 7016 Part V / IS: 1259]		<b>800</b>
	➤ Every Additional 50,000 Cycles		<b>575</b>